WMSR Series

WallMax® Module Solid Rounded



WallMax® Module Solid Rounded

WallMax® Modules Solid Rounded are designed to finish the sealing in the rounded edges of rounded rectangular frames (WRFR Series, see pg. 46).
WallMax® Modules Solid Rounded have a depth of 60mm.
WMSR modules must be used in combination with WRFR.

Modulo Solido Arrotondato WallMax®

I Moduli Solidi Arrotondati WallMax® sono pensati per terminare la sigillatura nei bordi delle cornici con angoli arrotondati (WRFR Series, guardare pg. 46).
I Moduli Solidi Arrotondati WallMax® hanno una profondità di 60 mm.
La gamma di moduli WMSR è pensata per l'utilizzo con cornici WRFR.

MATERIAL	MATERIALE
EPDM Rubber	Gomma EPDM

WMSR series

CODE CODICE	ARTICLE ARTICOLO	EXTERNAL DIMENSIONS (mm) DIMENSIONI ESTERNE (mm) HxWxR (D=60mm)	WEIGHT PESO g	 lb
71 6003 2020	WMSR 20 R2	20x20x20	22	0.049
71 6003 2040	WMSR 40 R4	40x40x40	61	0.134
71 6003 2060	WMSR 60 R6	60x60x60	87	0.192

NOTE: Weights are approximate.
NOTA: I pesi dichiarati sono indicativi.

WallMax®
PRODUCT CATALOGUE

